



優必克科技股份有限公司
UBIQ Technology Co., Ltd.

330桃園市桃園區大業路一段18號6樓之1

6F.-1, No.18, Sec. 1, Daye Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C.)

電話Tel : 03-331-2677 e-mail: sales@ubiq.com.tw

傳真Fax : 03-335-7412 Website: www.ubiq.com.tw

Separator

Application : For lithium battery



■ Separator (ND420)

Model : ND420

Specification : Thickness 20um, Width 63mm, Length 500M

Material : PE

■ Separator (C2325)

Model : C2325

Specification : Thickness 25 μ m, Width 63mm, Length 750M

Material : PP/PE/PP

Porosity : 39%

■ Separator (C2400)

Model : C2400

Specification : Thickness 25 μ m, Width 63mm, Length 750M

Material : PP

Porosity : 41%



優必克科技股份有限公司
UBIQ Technology Co., Ltd.

330桃園市桃園區大業路一段18號6樓之1

6F.-1, No.18, Sec. 1, Daye Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C.)

電話Tel : 03-331-2677 e-mail: sales@ubiq.com.tw

傳真Fax : 03-335-7412 Website: www.ubiq.com.tw

■ Separator (C2500)

Model : C2500

Specification : Thickness 25 μ m, Width 63mm, Length 750M

Material : PP

Porosity : 55%

■ Separator (CM824)

Model : CM824

Specification : Thickness 12 μ m, Width 63mm, Length 750M

Material: PP/PE/PP

■ Separator (NanoBase2)

Model: FPC3018

Specification : Thickness 30 μ m, Width 138mm, Length 10M

Material: Cellulose/Polyester

■ PTFE Separator

Specification : Thickness About 300 μ m, Diameter 47mm

Quantity : 100 piece/box



優必克科技股份有限公司
UBIQ Technology Co., Ltd.

330桃園市桃園區大業路一段18號6樓之1

6F.-1, No.18, Sec. 1, Daye Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C.)

電話Tel : 03-331-2677 e-mail: sales@ubiq.com.tw

傳真Fax : 03-335-7412 Website: www.ubiq.com.tw

■ **Non-Woven Separator (Ceramic Coating) (OZ-S25)**

Model : OZ-S25

Specification : Thickness 25 μ m, Width 156mm, Length 10M

Tensile strength : 1200 N/m

Porosity : 56%

Thermal shrinkage MD : < 5.0 (180°C/30mins)

Temperature resistance : 270°C

Application : Lithium ion battery

Material : PE + ceramic coating

■ **Non-Woven Separator (Ceramic Coating) (OZ-S30)**

Model : OZ-S30

Specification : Thickness 30 μ m, Width 202mm, Length 10M

Tensile strength : 1500 N/m

Porosity : 55%

Thermal shrinkage MD : < 5.0 (180°C/30mins)

Temperature resistance : 270°C

Application : Lithium ion battery

Material : PE + ceramic coating