



優必克科技股份有限公司
UBIQ Technology Co., Ltd.

330桃園市桃園區大業路一段18號6樓之1

6F.-1, No.18, Sec. 1, Daye Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C.)

電話Tel : 03-331-2677 e-mail: sales@ubiq.com.tw

傳真Fax : 03-335-7412 Website: www.ubiq.com.tw

加熱型輥壓機

型號: HRL-2300A



規格:

- 1.電源：三相AC 220V / 60Hz，功率約4KW
- 2.輥輪溫度：90°C (Max)，雙輥輪可獨立加熱及設定溫度
- 3.輥輪尺寸：Φ150mm×230mm
- 4.輥輪硬度：表面研磨鍍鉻，硬度>HRC63
- 5.輥輪同心度：± 3μm (間隙公差可能隨溫度升高而變化)
- 6.有效間隙：0.02 ~1.0mm，附兩支百分表可即時調整及觀察
- 7.輥壓速度：0~0.6米/分可調
- 8.工作寬度：210mm (Max)
- 9.最大壓力：5 ton
- 10.溫度精度：± 3°C
- 11.附工作台及底輪
- 12.重量：約350Kg
- 13.外觀尺寸：長*寬*高 約100 cm x 60 cm x 145 cm
- 14.前後壓克力板防護 (進料及出料口)
- 15.輥輪具有正反轉功能，有獨立開關可切換
- 16.含緊急停止裝置



優必克科技股份有限公司
UBIQ Technology Co., Ltd.

330桃園市桃園區大業路一段18號6樓之1

6F.-1, No.18, Sec. 1, Daye Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C.)

電話Tel : 03-331-2677 e-mail: sales@ubiq.com.tw

傳真Fax : 03-335-7412 Website: www.ubiq.com.tw

Electric Hot Rolling Press

Model: HRL-2300A



Specifications:

1. Power supply: Three-phase AC 220V / 60Hz, power about 4KW
2. Temperature : 90°C (Max), double rollers can be heated and set the temperature independently
3. Size: $\Phi 150\text{mm} \times 230\text{mm}$
4. Hardness of Roller : Surface grinding and chrome plating, hardness > HRC63
5. Rolling Concentricity : $\pm 3\mu\text{m}$ (gap tolerance may change with temperature increase)
6. Effective gap: 0.02 ~ 1.0mm, with two dial indicators for instant adjustment and observation
7. Rolling speed: 0~0.6 m/min adjustable
8. Working width: 210mm (Max)
9. Maximum pressure: 5 ton
10. Temperature accuracy: $\pm 3^\circ\text{C}$
11. With table and bottom wheel



優必克科技股份有限公司
UBIQ Technology Co., Ltd.

330桃園市桃園區大業路一段18號6樓之1

6F.-1, No.18, Sec. 1, Daye Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C.)

電話Tel : 03-331-2677 e-mail: sales@ubiq.com.tw

傳真Fax : 03-335-7412 Website: www.ubiq.com.tw

Electric Hot Rolling Press

Model: HRL-2300A

Specifications:

12. Net Weight : About 350Kg
13. Dimensions : L*W*H about 100 cm x 60 cm x 145 cm
14. Front and rear acrylic sheet protection (feed and discharge ports)
15. The roller has the function of forward and reverse rotation, and there is an independent switch to switch
16. With emergency stop device