



優必克科技股份有限公司
UBIQ Technology Co., Ltd.

330桃園市桃園區大業路一段18號6樓之1

6F.-1, No.18, Sec. 1, Daye Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C.)

電話Tel : 03-331-2677 e-mail: sales@ubiq.com.tw

傳真Fax : 03-335-7412 Website: www.ubiq.com.tw

輥壓機

型號：RL-3000A

製造商：UBIQ (Taiwan)

一：規格

- 1、輥輪尺寸： $\varnothing 150 \times 200 \text{mm}$
- 2、輥輪硬度：表面研磨鍍鉻，
硬度HRC63
- 3、輥輪同心度： $\pm 2 \mu\text{m}$
- 4、有效間隙：0.01-3mm可調
- 5、工作速度：0-3米/分可調
- 6、工作寬度：最大180mm
- 7、電壓：3相220V，電流5A (功率1kw)
- 8、輥輪壓力：3 T
- 9、可自動或手動(寸動)切換
- 10、在自動模式下具有正轉及停止功能
(按正轉鍵：滾壓機自動持續正轉，
直到按停止鍵停止轉動)
- 11、在手動模式下具有正轉及反轉功能
(需持續按壓才會轉動，一放開立即
停止，即所謂寸動裝置，可正向及
反向寸動，方便設備保養及清潔)
- 12、含2支厚薄規(測厚範圍0.03~0.5mm，13支
葉片，長10cm，日製或同等級)





優必克科技股份有限公司
UBIQ Technology Co., Ltd.

330桃園市桃園區大業路一段18號6樓之1

6F.-1, No.18, Sec. 1, Daye Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C.)

電話Tel : 03-331-2677 e-mail: sales@ubiq.com.tw

傳真Fax : 03-335-7412 Website: www.ubiq.com.tw

Rolling press

Model : RL-3000A

Manufacturer : UBIQ (Taiwan)



1. Roller Dimensions : $\varnothing 150 \times 200$ mm
2. Hardness Of Roller: Chrome plated surface, with HRC63
3. Rolling concentricity: $\pm 2\mu$ m
4. Rolling Gap : 0.01-3mm adjustable
5. Rolling Speed : 0~3m/min adjustable
6. Rolling Width : 180mm Max
7. Working Voltage: AC 220V Three Phase, Current value 5A (Power of battery 1kw)
8. Rolling Pressure: 3 Ton
9. Mode switch (Automatic and Manual)
10. With forward and stop function in automatic mode
(Press the start key : The rolling press starts automatically, until press the stop button to stop the machine.)
11. With forward and reverse function in manual mode
(It needs to be pressed continuously to turn, and it will stop immediately as soon as stop pressing the button, it be called inching device that features are maintenance and cleaning equipment)
12. With 2 pcs (Thickness 0.03~0.5mm, 13 brades, Length : 10 cm, Made in Japan or same grade)