



優必克科技股份有限公司
UBIQ Technology Co., Ltd.

330桃園市桃園區大業路一段18號6樓之1

6F.-1, No.18, Sec.1, Daye Rd., Taoyuan Dist., Taoyuan City 330, Taiwan

Tel : 03-331-2677 e-mail: sales@ubiq.com.tw

Fax : 03-335-7412 Website: www.ubiq.com.tw

鈕扣型電池封口機

型號：C2000-A

規格:

1. 符合CR2032電池封口。
2. 搭配手套箱內作業，由上而下，一段式壓合。
3. 手動機械式出力，壓合力需達250kgf。
4. 壓合後直徑 $20\pm 0.1\text{mm}$ ，高度 $3.2\pm 0.1\text{mm}$ 。
5. 下蓋鉚合後高度為 $2.6\pm 0.05\text{mm}$ 。
6. 電池退出設計需為下壓式槓桿，電池退出省力，不易卡住。
7. 上下模具為中空設計，上模可獨立拆下保養(不需拆下模)，且具有快拆模式(儘需要轉一顆螺絲，上模即可快速拆下)。
8. 外觀尺寸：約 H 450mm* L 340mm* W 335mm
9. 組合後電池，不可短路及洩漏。
10. 外觀鋼材/模具鋼材(硬化防銹處理)。





UBIQ Technology Co., Ltd.

6F.-1, No.18, Sec. 1, Daye Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C.)

Tel : +886-3-3312677 e-mail: sales@ubiq.com.tw

Fax : +886-3-3357412 Website: www.ubiq.com.tw

Sealing Machine for

CR2032

Model : C2000-A

Features :



1. For CR2032 case
2. With the glove box operation, one-step pressing from top to bottom
3. Manual mechanical output, pressure force to 250 kgf
4. After pressing, the diameter is $20 \pm 0.1\text{mm}$ and the height is $3.2 \pm 0.1\text{mm}$
5. The height after sealing is $2.6 \pm 0.05\text{mm}$
6. Battery-exit design is required for the lower pressure leverage, the battery quit effortlessly, operate easily
7. The upper and lower mold is a hollow design, the upper can be removed and maintained independently, and a mode that release quickly (just turn a screw, the upper can be quickly removed)
8. Size : About H 450mm* L 340mm* W 335mm
9. PTFE Anti-Corrosion Core prevents coin cells from being short-circuited
10. Heavy-duty steel frame ◦